WHAT IS CLAIMED IS:

1. A speech synthesizing apparatus for synthesizing a speech signal corresponding to a text, comprising:

behavior-state changing means for changing a behavior state according to a behavior model;

emotion-state changing means for changing an emotion state according to an emotion model;

selecting means for selecting control information according to at least one of the behavior state and the emotion state; and

synthesizing means for synthesizing a speech signal corresponding to the text according to speech synthesizing information included in the control information selected by the selecting means.

- 2. A speech synthesizing apparatus according to Claim
 1, wherein the speech synthesizing information includes at
 least one of a segment-data ID, a syllable-set ID, a pitch
 parameter, a parameter of the intensity of accent, a
 parameter of the intensity of phrasify, and an utterancespeed parameter.
- 3. A speech synthesizing apparatus according to Claim

 1, further comprising detecting means for detecting an

external condition,

wherein the selecting means selects the control information also according to the result of detection achieved by the detecting means.

4. A speech synthesizing apparatus according to Claim

1, further comprising holding means for holding individual information, and

wherein the selecting means selects the control information also according to the individual information held by the holding means.

5. A speech synthesizing apparatus according to Claim

1, further comprising counting means for counting the elapsed time from activation, and

wherein the selecting means selects the control information also according to the elapsed time counted by the counting means.

6. A speech synthesizing apparatus according to Claim
1, further comprising accumulating means for accumulating at
least one of the number of times the behavior-state changing
means changes behavior states and the number of times the
emotion-state changing means changes emotion states, and

wherein the selecting means selects the control

information also according to the number of times accumulated by the accumulating means.

- 7. A speech synthesizing apparatus according to Claim 1, further comprising substituting means for substituting for words included in the text by using a word substitute dictionary corresponding to selection information included in the control information selected by the selecting means.
- 8. A speech synthesizing apparatus according to Claim
 1, further comprising converting means for converting the
 style of the text according to a style conversion rule
 corresponding to selection information included in the
 control information selected by the selecting means.
- 9. A speech synthesizing apparatus according to Claim
 1, wherein the speech synthesizing apparatus is a robot.
- 10. A speech synthesizing method for a speech synthesizing apparatus for synthesizing a speech signal corresponding to a text, comprising:
- a behavior-state changing step of changing a behavior state according to a behavior model;

an emotion-state changing step of changing an emotion state according to an emotion model;

a selecting step of selecting control information according to at least one of the behavior state and the emotion state; and

a synthesizing step of synthesizing a speech signal corresponding to the text according to speech synthesizing information included in the control information selected by the process of the selecting step.

A recording medium storing a computer-readable speech-synthesizing program for synthesizing a speech signal corresponding to a text, the program comprising:

a behavior state changing step of changing a behavior state according to a behavior model;

an emotion-state changing step of changing an emotion state according to an emotion model;

a selecting step of selecting control information according to at least one of the behavior state and the emotion state; and

a/synthesizing step of synthesizing a speech signal corresponding to the text according to speech synthesizing information included in the control information selected by the process of the selecting step.